



NC30 UC nut crimping machines produce accurate and consistent results when crimping the nuts, ferrules and bushings on ends of hydraulic hoses. Their various serviceable features make them suitable for serial production.



Crimping Range: 12 - 63mm



66 tons of crimping force



Hose size up to 2"

TECHNICAL SPECS

DESCRIPTION	NC30 UC
Crimping range \varnothing (mm)	12-63
Crimping force (kN)	660
Number of crimps/hour ³	2400
Hose size ID (inch)	2"
Die type ^{1,4}	NC30
Max opening ² (mm)	+26
Master die shoe length (mm)	35
Motor (kW)	4
Dimensions	
width (mm)	885
length (mm)	835
height (mm)	997
Weight (kg)	240

1. See table for standard die set data
 2. Min. crimping dia. of die set added by table value
 3. Theoretical with 1/2" hose \varnothing 10 mm
 4. NC30 dies can be used with adapter dies
- *Subject to change without prior notice

STANDARD DIE SETS*

CODE	CRIMPING DIAMETER (MM)	LENGTH (MM)
702044/12	12.0 - 14.0	3
702044/14	14.0 - 16.0	3
702044/16	16.0 - 19.0	4
702044/19	19.0 - 22.0	4
702044/22	22.0 - 26.0	4.5
702044/26	26.0 - 30.0	4.5
702044/30	30.0 - 34.0	5
702044/34	34.0 - 39.0	5
702044/39	39.0 - 45.0	5
702044/45	45.0 - 51.0	5
702044/51	51.0 - 57.0	5
702044/57	57.0 - 63.0	5

*In addition to the standard die sets, a wide range of special die sets for different diameters, lengths and forms is available

OPCIONAL EXTRAS



LONG LIFE

Auto greasing system



EASY POSITIONING

Mechanical back stop device

UC CONTROL




UC1

Pressure crimping



UC2

Multi-step crimping



UC3

Data report