

P32X

PRENSADORA | CRIMPING

FINN-POWER
Crimping since 1973



Finn-Power P20X and P32X crimping machines are cost-effective alternatives for single-piece production.

Finn-Power P-models (precision, durability, force and ease of use), the P32X model is totally unmatched in it's own class.



Crimping Range: 10 - 87mm



200 tons of crimping force



Hose size up to 2"

TECHNICAL SPECS

DESCRIPTION	P32X
Hose size	2"
Crimping range (mm)	10-87
Die type ¹	32
Max opening (mm) ²	+33
Master die shoe length (mm)	80
Motor (kW) ³	2.2
Standard voltages (V) ^{4,5}	230 or 400
Crimping force (kN)	2000
Noise level (dB(A))	71
Protection class	IP54
Overall dimensions:	
width (mm)	521
length (mm)	632
height (mm)	567
Weight without oil (kg)	143

STANDARD DIE SETS*

CODE	CRIMPING DIAMETER (MM)	LENGTH (MM)	CODE	CRIMPING DIAMETER (MM)	LENGTH (MM)
32-10	10.0 - 12.0	55	20-34	34.0 - 39.0	75
32-12	12.0 - 14.0	55	20-39	39.0 - 45.0	75
32-14	14.0 - 16.0	55	20-45	45.0 - 51.0	90
32-16	16.0 - 19.0	55	20-51	51.0 - 57.0	90
32-19	19.0 - 22.0	70	20-57	57.0 - 63.0	100
32-22	22.0 - 26.0	70	20-63	63.0 - 69.0	110
32-26	26.0 - 30.0	70	20-69	69.0 - 75.0	110
32-30	30.0 - 34.0	70	20-74	74.0 - 80.0	110
			20-78	78.0 - 87.0	110

1. See table for standard die set data
2. This tabular value must be added to min.crimping dia. of die set
3. 1-phase 1.5 kW
4. 1-phase 100 or 230 V
5. Other voltages upon request

* In addition to the standard die sets, a wide range of special die sets for different diameters, lengths and forms is available

OPCIONAL EXTRAS



CONVENIENCE

Adjustable control unit



SPEED

Quick change and QC Tool base



EASY POSITIONING

Mechanical back stop device