CONEXIONES HYPERSPIRAL

BOSADO

RACORERÍA NO PELAR - HYPERSPIRAL / *FITTINGS NO SKIVE - HYPERSPIRAL*

ÍNDICE		INDEX
Casquillos para prensar	**4**	Crimped sleeves
Rosca BSP y NPT	**4**	BSP and NPT thread
Rosca métrica - Serie ligera - asiento 24°	**5**	Metric thread - Light series - 24° seat
Rosca métrica - S/ Pesada - Asiento 24°	**5**	Metric thread - Heavy series - 24° seat
Rosca JIC	**6**	JIC thread
Rosca ORFS	**6**	ORFS thread
Bridas 3000 PSI (SAE J 518)	**7**	3000 PSI flanges (SAE J 518)
Bridas 6000 PSI (SAE J 518)	**7**	6000 PSI flanges (SAE J 518)
Bridas Caterpillar	**7**	Caterpillar flanges
Huellas de prensado	**8**	Crimped pressure

Importante: Grupo BOSADO se reserva el derecho de **modificación de precios** y referencias sin previo aviso. Por favor, consulte y contraste el precio vigente antes de realizar su pedido.

Los precios son expresados en **euros** y corresponden a cada unidad de producto. Los gastos derivados del envío no están incluidos.

Consúltenos si no encuentra el producto que busca. Somos especialistas en fabricación de piezas bajo plano.

Important: BOSADO Group reserves the right to **modify prices** and references without prior notice. Please consult and contrast the current price before placing your order.

The prices are expressed in **euros** and correspond to each unit of product. Shipping costs are not included.

Ask us if you can not find the product you are looking for. We are specialists in the manufacture of tlored parts.

RACORES NO PELAR - HYPERSPIRAL
FITTINGS NO SKIVE - HYPERSPIRAL

CASQUILLO NO PELAR
SLEEVES NO SKIVE

Mangueras:
- EN 856 **4SP**
- EN 856 **4SH**
- SAE 100 **R15**

Manguera *Hose*			4SP - 4SH -R15
Ø Int. tubo *Ø Int. Tube* Pulgada *Inch*	mm.	Ref. Galga *Dash*	NP04000 PVP / und.
3/8"	9,5	06 ■	
1/2"	12,8	08 ■	
5/8"	16,0	10 ■	
3/4"	19,0	12 ■■■	
1"	25,4	16 ■■■	
1 1/4"	31,8	20 ■	
1 1/4"	31,8	6-20 ■	

ROSCA BSP / NPT
BSP/NPT THREAD







			Macho BSP cilíndrico	Tuerca BSP giratoria recta	Tuerca BSP giratoria 45°	Tuerca BSP giratoria 90°		Macho NPT cónico
	Referencia *Reference*		NP35510	NP45512●	NP45542●	NP45592●	Referencia *Reference*	NP37810
Øint.Mang *Ø Int. Hose*	Rosca/*Thread* BSP	Galga *Dash*	PVP / und.				Rosca NPT *NPT Thread*	PVP / und.
3/8"	3/8"-19h	06-06					3/8"-18h	
3/8"	1/2"-14h	06-08					1/2"-14h	
1/2"	3/8"-19h	08-06					3/8"-18h	
1/2"	1/2"-14h	08-08					1/2"-14h	
1/2"	5/8"-14h	08-10					-	
1/2"	3/4"-14h	08-12					3/4"-14h	
5/8"	1/2"-14h	10-08					1/2"-14h	
5/8"	5/8"-14h	10-10					-	
5/8"	3/4"-14h	10-12					3/4"-14h	
5/8"	1"-11h	10-16					1"-11,5h	
3/4"	1/2"-14h	12-08					1/2"-14h	
3/4"	3/4"-14h	12-10					-	
3/4"	3/4"-14h	12-12					3/4"-14h	
3/4"	1"-11h	12-16					1"-11,5h	
1"	3/4"-14h	16-12					3/4"-14h	
1"	1"-11h	16-16					1"-11,5h	
1"	1 1/4"-11h	16-20					1 1/4"-11,5h	
1 1/4"	1 1/4"-11h	20-20					1 1/4"-11,5h	
1 1/4"	1 1/2"-11h	20-24					1 1/2"-11,5h	

Tuerca prensada *Swaging nut* ● Multiespiral *Multispiral* ● Tuerca desplazable *Travelling nut* ● Tuerca engargolada *Wire nut* ●

Sin precio u otras medidas, consultar. Somos fabricantes

BOSADO

ROSCA MÉTRICA - SERIE LIGERA - ASIENTO 24°

METRIC THREAD - LIGHT SERIES - 24° SEAT






Referencia *Reference*				Macho Métrico S/Ligera 24°	Tuerca giratoria recta S/Ligera 24° O´ring	Tuerca giratoria 45° S/Ligera 24° O´ring	Tuerca giratoria 90° S/Ligera 24° O´ring
				NP36110	NP46512●	NP46542●	NP46592●
Øint.Mang *Ø Int. Hose*	Rosca Mét *Met. Thread*	ØTubo *Ø Tube*	Galga *Dash*	PVP / und.			
3/8″	16 x 1.5	Ø 10	06-16				
3/8″	18 x 1.5	Ø 12	06-18				
3/8″	22 x 1.5	Ø 15	06-22				
1/2″	18 x 1.5	Ø 12	08-18				
1/2″	22 x 1.5	Ø 15	08-22				
1/2″	26 x 1.5	Ø 18	08-26				
5/8″	26 x 1.5	Ø 18	10-26				
5/8″	30 x 2	Ø 22	10-30				
3/4″	26 x 1.5	Ø 18	12-26				
3/4″	30 x 2	Ø 22	12-30				
3/4″	36 x 2	Ø 28	12-36				
1″	36 x 2	Ø 28	16-36				
1 1/4″	45 x 2	Ø 35	20-45				

ROSCA MÉTRICA - SERIE PESADA - ASIENTO 24°

METRIC THREAD - HEAVY SERIES - 24° SEAT






Referencia *Reference*				Macho Métrico S/Pesada 24°	Tuerca giratoria recta S/Pesada 24° O´ring	Tuerca giratoria 45° S/Pesada 24° O´ring	Tuerca giratoria 90° S/Pesada 24° O´ring
				NP36210	NP46612●	NP46642●	NP46692●
Øint.Mang *Ø Int. Hose*	Rosca Mét *Met. Thread*	ØTubo *Ø Tube*	Galga *Dash*	PVP / und.			
3/8″	18 x 1.5	Ø 10	06-18				
3/8″	20 x 1.5	Ø 12	06-20				
3/8″	22 x 1.5	Ø 14	06-22				
1/2″	22 x 1.5	Ø 14	08-22				
1/2″	24 x 1.5	Ø 16	08-24				
1/2″	30 x 2	Ø 20	08-30				
5/8″	30 x 2	Ø 20	10-30				
5/8″	36 x 2	Ø 25	10-36				
3/4″	30 x 2	Ø 20	12-30				
3/4″	36 x 2	Ø 25	12-36				
3/4″	42 x 2	Ø 30	12-42				
1″	36 x 2	Ø 25	16-36				
1″	42 x 2	Ø 30	16-42				
1 1/4″	42 x 2	Ø 30	20-42				
1 1/4″	52 x 2	Ø 38	20-52				

RACORES NO PELAR - HYPERSPIRAL
FITTINGS NO SKIVE - HYPERSPIRAL

ROSCA JIC
JIC THREAD






			Macho recto cilíndrico JIC	Tuerca giratoria recta JIC	Tuerca 45° giratoria JIC	Tuerca 90° giratoria JIC
	Referencia *Reference*		NP37510	NP47512●	NP47542●	NP47592●
Øint.Mang *Ø Int. Hose*	Rosca JIC *JIC Thread*	Galga *Dash*	PVP / und.			
3/8"	9/16"-18h	06-06				
3/8"	3/4"-16h	06-08				
3/8"	7/8"-14h	06-10				
1/2"	3/4"-16h	08-08				
1/2"	7/8"-14h	08-10				
1/2"	1 1/16"-12h	08-12				
5/8"	7/8"-14h	10-10				
5/8"	1 1/16"-12h	10-12				
3/4"	7/8"-14h	12-10				
3/4"	1 1/16"-12h	12-12				
3/4"	1 3/16"-12h	12-14				
3/4"	1 5/16"-12h	12-16				
1"	1 1/16"-12h	16-12				
1"	1 5/16"-12h	16-16				
1"	1 5/8"-12h	16-20				
20	1 5/16"-12h	20-16				
1 1/4"	1 5/8"-12h	20-20				
1 1/4"	1 7/8"-12h	20-24				

ROSCA ORFS
ORFS THREAD






			Macho recto cilíndrico ORFS	Tuerca giratoria recta ORFS	Tuerca 45° giratoria ORFS	Tuerca 90° giratoria ORFS
	Referencia *Reference*		NP32413	NP47411●	NP47441●	NP47491●
Øint.Mang *Ø Int. Hose*	Rosca ORFS *ORFS. Thread*	Galga *Dash*	PVP / und.			
3/8"	9/16"-18h	06-04				
3/8"	11/16"-16h	06-06				
3/8"	13/16"-16h	06-08				
3/8"	1"-14h	06-10				
1/2"	11/16"-16h	08-06				
1/2"	13/16"-16h	08-08				
1/2"	1"-14h	08-10				
1/2"	1 13/16"-12h	08-12				
5/8"	1"-14h	10-10				
5/8"	1 13/16"-12h	10-12				
3/4"	1"-14h	12-10				
3/4"	1 13/16"-12h	12-12				
3/4"	1 7/16"-12h	12-16				
3/4"	1 11/16"-12h	12-20				
1"	1 3/16"-12h	16-12				
1"	1 7/16"-12h	16-16				
1"	1 11/16"-12h	16-20				
1 1/4"	1 11/16"-12h	20-20				
1 1/4"	2"-12h	20-24				

Tuerca prensada ● *Swaging nut* | Multiespiral ● *Multispiral* | Tuerca desplazable ● *Travelling nut* | Tuerca engargolada ● *Wire nut*
Sin precio u otras medidas, consultar. Somos fabricantes

BRIDAS 3000 - 6000 PSI (SAE J 518)

3000 -6000 PSI FLANGES (SAE J 518)

			3000 PSI			6000 PSI		
								
			Brida Recta 3000 PSI	Brida 45° 3000 PSI	Brida 90° 3000 PSI	Brida Recta 6000 PSI	Brida 45° 6000 PSI	Brida 90° 6000 PSI
Referencia *Reference*			NP48310	NP48340	NP48390	NP48610	NP48640	NP48690
Øint.Mang *Ø Int. Hose*	Galga *Dash*	Brida *Flange*	PVP / und.			Brida *Flange*	PVP / und.	
1/2"	08-08	Ø 30,2				Ø 31,7		
1/2"	08-10	Ø 34,0						
1/2"	08-12	Ø 38,1				Ø 41,3		
5/8"	10-08	Ø 30,2				Ø 31,7		
5/8"	10-10	Ø 34,0						
5/8"	10-12	Ø 38,1				Ø 41,3		
3/4"	12-08	Ø 30,2						
3/4"	12-12	Ø 38,1				Ø 41,3		
3/4"	12-16	Ø 44,5				Ø 47,6		
1"	16-12	Ø 38,1				Ø 41,3		
1"	16-16	Ø 44,5				Ø 47,6		
1"	16-20	Ø 50,8				Ø 54,0		
1 1/4"	20-20	Ø 50,8				Ø 54,0		
1 1/4"	20-24	Ø 60,3				Ø 63,5		

BRIDAS CATERPILLAR

CATERPILLAR FLANGES

			Caterpillar		
					
			Brida Recta 6000 PSI	Brida 45° 6000 PSI	Brida 90° 6000 PSI
Referencia *Reference*			NP48614	NP48644	NP48694
Øint.Mang *Ø Int. Hose*	Galga *Dash*	Brida *Flange*	PVP / und.		
3/4"	12-12	Ø 41,3			
3/4"	12-16	Ø 47,6			
1"	16-16	Ø 47,6			
1"	16-20	Ø 54,0			
1 1/4"	20-20	Ø 54,0			
1 1/4"	20-24	Ø 63,5			

HUELLAS DE PRENSADO CASQUILLOS Y CONEXIONES HYPERSPIRAL				
REFERENCIA MANGUERA	DN	GALGA	CASQUILLO	HUELLA DE PRENSADO
4290/BSD 4290 DIN EN 856/4SP SAE 100 R9R	10	6	NP04000-06	**26,1**
	13	8	NP04000-08	**29,0**
	16	10	NP04000-10	**34,2**
	19	12	NP04000-12	**37,5**
	25	16	NP04000-16	**46,5**
6271/BSD 6271 SAE 100 R15	19	12	NP04000-12	**37,5**
	25	16	NP04000-16	**46,5**
	31	20	NP04000/6-20	**58,5**
4270/BSD 4270 DIN EN 856/4SH	19	12	NP04000-12	**37,5**
	25	16	NP04000-16	**46,3**
	31	20	NP04000-20	**55,4**

TOLERANCIAS: Diámetro de Prensado: 0/-0.2mm
Diámetros aproximados, necesario probar.

Cotas en mm. rev.d) 14/04/2021

Notas:

COMERCIAL
C/ Nivel, 12-3. P. I. Store
41008 - Sevilla (Spn)
Tlfn: (0034) 954 358 149
Fax: (0034) 954 357 401
bosado@bosado.com

FABRICACIÓN
C/ Gramil, 14-5. P. I. Store
41008 - Sevilla (Spn)
Tlfn: (0034) 954 353 271
Fax: (0034) 954 433 714
tbosado@bosado.com

bosado.com